

Technical Specifications for Cassette Airconditioning

		1.5 TR	2 TR	3 TR	4 TR
Model No.	Units	SCR-181YD	SCR-241YD	SCR-361RD	SCR-481RD
Cooling Capacity	BTU/Hr	18000	24000	36000	48000
	KCAL/Hr	4500	6000	9000	12000
	TR	1.5	2	3	4
Indoor Unit					
Body Dimensions (W x D x H)	mm	840 x 840 x 240	840 x 840 x 240	840 x 840 x 310	840 x 840 x 310
Panel Dimensions (W x D x H)	mm	950 x 950 x 40	950 x 950 x 40	950 x 950 x 40	950 x 950 x 40
Cooling Coil		Inner grooved copper, hydrophilic blue fins			
Blower Fan		Centrifugal Type			
Nominal Airflow High / Low	CMH	1000 / 830	1050 / 900	1600 / 1420	1750 / 1500
	CFM	600 / 490	620 / 530	950 / 850	1050 / 890
Indoor Noise Level	DbA	43/40	43/40	47/44	47/44
Fan Speed		2	2	2	2
Moisture Removal	Litres / Hour	1.9	2.4	4	4.4
Control		Cordless Remote - Microprocessor Control			
Power Supply		230 V / 1 PH / 50 Hz			
Net / Gross Weight	Kg	36/46	36/46	40/50	40/50
Net / Gross Weight	Kg	6 / 11	6 / 11	6 / 11	6 / 11
Outdoor Unit					
Electric Power Supply		230V/1PH/50Hz	230V/1PH/50Hz	415v/1PH/50Hz	415v/1PH/50Hz
Compressor		Rotary	Rotary	Rotary	Rotary
Connection - Suction	Inches	1 / 2	5 / 8	3 / 4	3 / 4
Connection - Liquid	Inches	1 / 4	3 / 8	1 / 2	1/2
Dimensions (W x D x H)	mm	850 x 335 x 540	850 x 335 x 540	1020 x 415 x 650	1020 x 415 x 650
Net / Gross Weight	Kg	50	69	80	110